

November 14, 2016 Hearing Protective Device Test Report Number Q4261A Revision 0



MRI Audio  
Attn: Spencer Howe  
2720 Loker Avenue West Suite N  
Carlsbad, CA 92010

Lab Code 100427-0  
Date of Sample Receipt: 11/2/16  
Date of tests: 11/3/16-11/11/16


Attenuation measurements have been performed according to the American National Standards Institute (ANSI) Specifications, ANSI S3.19-1974, using the experimenter-fit protocol, on the MRI Audio Headset muff-type hearing protector (test ID Q4261A). The specified threshold measurement data were obtained using ten normal-hearing listeners, six male and four female. These listeners were selected from a standby group of about 35 volunteers who regularly serve as listeners for measurements of this kind.

The measurements were made in a room designed for this purpose. All acoustic characteristics of the room meet the requirements outlined in ANSI S3.19-1974. The ambient noise levels in this room are below the limits specified in ANSI S3.19-1974, and open ear thresholds are used on a continuing basis to monitor the background noise levels. An automatic recording attenuator was used to record both open and occluded ear thresholds.

Each of ten subjects was tested three times at each of nine test frequencies. The attached Tables show grand mean attenuation values in decibels (dB) for each test signal along with group attenuation values. Standard deviations (S.D.) for the 30 different attenuation determinations for each test signal are also given. The results presented in this report pertain to the samples tested only.

Michael & Associates is accredited by the National Institute of Standards and Technology (NIST) National Laboratory Accreditation Program (NVLAP) for tests performed according to ANSI S3.19-1974, ANSI S12.6-2008 and AUS S1270:2002. These accreditation criteria encompass the requirements of international standard ISO 17025. This report may only be reproduced or transmitted electronically in its entirety. This report shall not be used to claim product endorsement by NIST, NVLAP or by any agency of the U.S. Government. All measurement equipment are calibrated with instrumentation traceable to the NIST.

*Use these laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.*

  
\_\_\_\_\_  
Kevin Michael, Ph.D.  
President

11/14/16  
\_\_\_\_\_  
Date

**Individual and Summary Attenuation Data for  
Hearing Protective Devices**

Test Method: ANSI S3.19-1974

Manufacturer: MRI Audio

Model: Headset

Position: Over-the-head

Date: 11/14/16

Test ID # Q4261A

FREQUENCY IN HERTZ

SUBJECT	125	250	500	1000	2000	3150	4000	6300	8000
1	22	28	38	38	38	37	39	42	42
	26	31	37	36	33	36	37	40	38
	28	30	36	41	34	34	38	40	42
2	22	23	34	40	34	37	33	37	31
	24	23	32	38	34	37	35	36	33
	21	24	33	39	36	36	33	34	37
3	19	27	35	46	37	37	35	39	37
	16	23	34	44	36	37	36	38	34
	18	27	34	45	37	38	37	37	36
4	22	27	37	43	35	39	37	37	37
	24	28	37	42	35	40	39	39	37
	22	27	35	43	36	40	37	38	37
5	24	24	32	41	38	36	35	35	36
	22	22	30	38	39	38	33	35	36
	22	23	33	40	37	34	33	34	34
6	28	25	33	39	39	38	36	40	38
	22	25	31	40	38	38	35	37	37
	22	23	33	43	36	37	37	37	34
7	20	22	39	41	36	36	39	42	37
	21	28	38	39	36	36	35	42	38
	22	27	39	39	37	37	40	45	38
8	22	25	31	40	35	39	38	34	37
	24	25	32	42	39	41	38	37	37
	26	27	33	38	38	40	37	36	38
9	17	26	36	44	35	32	37	38	41
	21	26	35	43	39	37	35	38	40
	20	27	36	44	37	34	31	36	33
10	29	25	34	43	35	38	37	39	37
	22	28	35	44	35	36	36	42	38
	23	25	33	41	36	37	36	38	40
MEANS	22.3	25.7	34.5	41.0	36.3	37.1	36.0	38.0	37.0
STD. DEV.	3.0	2.2	2.4	2.5	1.7	2.0	2.2	2.6	2.5

NRR = 29 dB

Headband force = 2.1 lbs

*Use these laboratory-derived data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.*

Manufacturer: MRI Audio  
Model: Headset  
Position: Over-the-head

Date: 11/14/16  
Test ID: Q4261A

Measurements were made according to American National Standards Institute Specifications ANSI S3.19-1974.

Center Frequency in Hz	Mean Attenuation in dB	Group Attenuation in dB	Standard Deviation in dB
125	22.3	48.0	3.0
250	25.7		2.2
500	34.5		2.4
1000	41.0		2.5
2000	36.3	184.9	1.7
3150	37.1		2.0
4000	36.0		2.2
6300	38.0	75.0	2.6
8000	37.0		2.5

Test Item: Q4261A



These data were obtained through measurements made at the laboratories of Michael & Associates, Inc., State College, PA , USA. Michael & Associates, Inc., is accredited to test to ANSI S3.19-1974, ANSI S12.6-2008, ANSI S12.42-2010, EN352 parts 1-8 and AS/NZ S1270:2002 by the National Institute of Standards and Technology (NIST) National Voluntary Laboratory Accreditation Program (NVLAP).

  
Kevin L. Michael, Ph.D.  
President

  
Date